

SMART VISOFOLD 1000 BI-FOLDING DOOR

Customer _____

Address: _____

Date Required: _____

REF: _____

Tel: _____

Aluminium Finish	White	Black	Grey	
	RAL Outside			
	RAL Inside			

Threshold Option	51mm Standard	
	15mm Low	
	Low Threshold No Weather Performance	

Frame Extension	Top	20mm	42mm	
	Left	20mm	42mm	
	Right	20mm	42mm	

Sub Cill	Cill	135mm	155mm	190mm
	Horn	50mm	100mm	
	(Optional If Threshold = Standard 51mm)			

Handle Colour	Standard Handle			
	White	Silver	Black	Chrome

Trickle Vent	Required	
	T/Vent Qty	
	(Optional If F/Ext'n - Top = 42mm)	

Bead	Square Bead Only
-------------	------------------

Glazing Option	DGU	Unglaed	Glazed	
	Safety	Tuff	Lam	
	Spacer	Black	White	Grey

Order Checked	Yes	No
----------------------	-----	----

Approved By	
--------------------	--

Size Limitation - Each Leaf
700mm < Door Width < 1100mm
1900mm < Door Height < 2400mm



DocL 2010 Compliance - u Value
1.8 W/m2K (Unless Specified) With 1.2 Glass Centre Pane U Value, Swiss Spacer V and Argon

CE Marking
All Glazed Products are CE Marked in Our Factory



Trickle Ventilation Location
Trickle vent will be fitted in 42mm frame extension @ top side.



Overall Width		Open In	
Overall Height		Open Out	

2 PANE



 2A  H2A



3 PANE


 3A  H3A

 3B  H3B



4 PANE



 4A  H4A



 4B  H4B

 4C



5 PANE



 5A  H5A



 5B  H5B

 5C  H5C



6 PANE



 6A  H6A



 6B  H6B

 6C  H6C

7 PANE

 7A  H7A

 7B  H7B

 7C  H7C